

## **MultiBiometric BioFace – Pro**



















Speedy Recognition avoids long queue

4" Touch Screen Display

Dual Wide Angle Camera for Live Body Sensing

WDR camera for low light imaging

Access Control features for integration with doors.

High accuracy facial recognition rate of >=99.27% & Recognition speed of

Can recognize faces from a distance of 4feet.

Strong & sturdy dustproof & splashproof metallic body. Asoavailable Mild steel Powder coated external casing for added protection.

Standard Battery backup of 2 hrs/24 hrs (optional)

## **Technical Specification**

12 VDC, 2A Operating Temp 0°C ~ 50°C Working Humidity 10%-90%RH Dimension 138x138x28 mm

Weigand In & Out Relay o/p Yes

Exit Reader Weigand, Push Switch

4" 800x480p Touch Screen Display 2Mp Binocular WDR camera Camera

Voice Instruction English, Hindi

Wi-Fi / TCP/IP / USB Communication

10,000. Finger Capacity **Face Capacity** 2,000. **Card Capacity** 2,000. **Password Capacity** 2,000. Log Capacity 2,00,000.

OS Linux

FP Sensor 500 DPI Optical 0.00001% FAR FRR 0.001%

Card Reader 125 KHz / 13.56 MHz

(Optional)

Authentication

Mode Face, Finger, Card,

Password

## ISHA SYSTEMS & SOFTWARE

C - 1014, STATION PLAZA, BHANDUP STATION ROAD, BHANDUP WEST, MUMBAI - 400 078, INDIA www.ishasystems.co.in

Email: sales@ishasystems.co.in

Tel: +91 81080 98745





