isha

MultiBiometric BioFace – Ultra

















- Speedy Recognition avoids long queue \sim
- Large 5" Touch Screen Display S
- Dual Wide Angle Camera for Live Body Sensing S

ISF

- WDR camera for low light imaging S
- Access Control features for integration with és doors.
- High accuracy facial recognition rate of $\langle \rangle$ >=99.27% & Recognition speed of <=0.2s.
- Can recognize faces from a distance of 4feet. Ś
- Strong & sturdy dustproof & splashproof S metallic body. Asoavailable Mild steel Powder coated external casing for added protection.
- Standard Battery backup of 2 hrs/24 hrs (optional) Jes 5

Technical Specification	Communication	Wi-Fi / TCP/IP / USB
Power 12 VDC, 2A Operating Temp 0°C ~ 50°C	Finger Capacity Face Capacity	10,000. 10,000.
Working Humidity 10%-90%RH	Card Capacity Password Capacity	10,000. 10,000. 10,000.
Dimension 205x82x30 mm	Log Capacity	2,00,000.
WeigandIn & OutRelay o/pYesExit ReaderWeigand, RS 485, Push SwitchDisplay5" 1280x720p Touch ScreenCamera2Mp Binocular WDR camera	OS FP Sensor FAR FRR Card Reader	Linux 500 DPI Optical 0.00001% 0.001% 125 KHz / 13.56 MHz (Optional)
Voice Instruction English, Hindi	Authentication Mode	MHz (Optional) Face, Finger, Card, Password

ISHA SYSTEMS & SOFTWARE

C - 1014, STATION PLAZA, BHANDUP STATION ROAD, BHANDUP WEST, MUMBAI - 400 078, INDIA Email: sales@ishasystems.co.in Tel: +91 81080 98745

www.ishasystems.co.in





